

DewTech 390 – High Precision Low DewPoint Chilled Mirror Hygrometer

APPLICATION: The **Model DewTech 390** is a precision Low Dew Point Chilled Mirror Hygrometer (measure down to -95C dew point) used in National and Private metrology labs, calibration houses and industrial quality operations.

DESCRIPTION: The DT390 is available as a bench or counter top configuration. At the core of the DT-390 is a precision chilled mirror hygrometer. The DT-390 is a self-contained low dew point measurement instrument with an integrated refrigeration system. Measurement of DP/FP is configurable in °C or °F, %RH, AT, ppm(v) and pressure. Dew Point range -95°C to +20°C (+/-0.2°C). Auto and programmable ABC functions, full LCD display, with front access to chilled mirror sensor. Outputs 0-5VDC, 4-20mA, 0-10VDC or 0-20mA, RS232. Includes NIST traceable calibration certificate, operation manual and 1 year warranty. Chrome Mirror, 1/4in VCR Fittings

DT390 DewTech 390 Table Top Version.....\$26,125.00



DT390-Rack DewTech 390 19" in Rack Mount Version.....\$26,125.00



Extended Warranty/Calibration Options: Please list as separate line items:

3EXTW	3 Year Extended Warranty includes repairs covered in the warranty statement	\$ 2,500.00
3YNIST1P	3 NIST Traceable Calibrations for the price of 2 (1 Parameter)	\$ 1,210.00